

# MJL Industrial, Inc.

## MAGNESIUM ACETATE

### MJ Mg-ACT

- ♣ Catalyst for manufacturing PTA and DMT
- ♣ Catalyst for PSF, PFY, Polyester Film and PET Bottle Resin production
- ♣ Mordant in dyeing, manufacturing of bister

### Typical Properties

### MJ Mg-ACT

Chemical Description	Magnesium Acetate Tetrahydrate
	Mg (CH <sub>3</sub> COO) <sub>2</sub> • 4H <sub>2</sub> O
Physical Appearance	White transparent monoclinic crystal
Purity:	99.0% Minimum
Calcium (Ca)	100 ppm Maximum
Iron (Fe)	20 ppm Maximum
Lead (Pb)	20 ppm Maximum
Chlorides	30 ppm Maximum
Sulfates	100 ppm Maximum
Water Insoluble	100 ppm Maximum

**Packaging:** 20 KG drum; or, 25 KG drum

**Identification:** CAS# 16674-78-5

UN# not regulated

**H.S. Tariff Code:** 2915.29.00

The above table gives typical analysis based on historical production performance. MJL does not make any express or implied warranty that future production will demonstrate or continue to possess these typical analysis.

---

405 Uxbridge Way, Hockessin, DE 19707, USA; Tel: +1 (302) 234-0898; Fax: +1 (302) 234-4167;  
E-mail: [webmaster@mjindustrial.com](mailto:webmaster@mjindustrial.com)

Revised: January 1, 2006