

# MJL Industrial, Inc.

## SODIUM ACETATE

### MJ Na-ACT

- ♣ Catalyst for manufacturing PTA and DMT
- ♣ Catalyst for PSF, PFY, Polyester Film and PET Bottle Resin production

### Typical Properties

### MJ Na-ACT

Chemical Description	Sodium Acetate Trihydrate	
	Na (CH <sub>3</sub> COO) <sub>2</sub> • 3H <sub>2</sub> O	
Physical Appearance	Crystal	
Sodium Acetate	98.5%	Minimum
Calcium (Ca)	50 ppm	Maximum
Iron (Fe)	5 ppm	Maximum
Lead (Pb)	10 ppm	Maximum
Chlorides	20 ppm	Maximum
Sulfates	20 ppm	Maximum
Water Insoluble	100 ppm	Maximum

**Packaging:** 25 KG plastic bag  
**Identification:** CAS# 6131-90-4  
UN# not regulated  
**H.S. Tariff Code:** 2915.22.00

The above table gives typical analysis based on historical production performance. MJL does not make any express or implied warranty that future production will demonstrate or continue to possess these typical analysis.

---

405 Uxbridge Way, Hockessin, DE 19707, USA; Tel: +1 (302) 234-0898; Fax: +1 (302) 234-4167;  
E-mail: [webmaster@mjlindustrial.com](mailto:webmaster@mjlindustrial.com)

Revised: January 1, 2006