

# MJL Industrial, Inc.

## ZINC ACETATE

### MJ Zn-ACT

- ♣ Catalyst for manufacturing PTA and DMT
- ♣ Catalyst for PSF, PFY, Polyester Film and PET Bottle Resin production using DMT route

### Typical Properties

### MJ Zn-ACT

Chemical Description	Zinc Acetate Dihydrate $\text{Zn}(\text{CH}_3\text{COO})_2 \cdot 2\text{H}_2\text{O}$	
Physical Appearance	Off-white crystal	
Zinc Acetate	98.5%	Minimum
Arsenic (As)	20 ppm	Maximum
Iron (Fe)	5 ppm	Maximum
Lead (Pb)	10 ppm	Maximum
Chlorides	30 ppm	Maximum
Sulfates	50 ppm	Maximum
Water Insoluble	0.01%	Maximum

**Packaging:** 20 KG or 25 KG plastic bag

**Identification:** CAS# 5970-45-6  
UN# not regulated

**H.S. Tariff Code:** 2915.29.50

The above table gives typical analysis based on historical production performance. MJL does not make any express or implied warranty that future production will demonstrate or continue to possess these typical analysis.

---

405 Uxbridge Way, Hockessin, DE 19707, USA; Tel: +1 (302) 234-0898; Fax: +1 (302) 234-4167;  
E-mail: [webmaster@mjindustrial.com](mailto:webmaster@mjindustrial.com)

Revised: January 1, 2006